



Chain No.	节距 Pitch	滚子直径 Roller diameter	内节内宽 Width between inner plates	销轴直径 Pin diameter	加长销尺寸 Extended pin dimension		销轴长度 Pin length		内链板高度 Inner plate depth	链板厚度 Plate thickness
	P	d ₁ max	b ₁ min	d ₂ max	d ₃ max	L ₃	L max	L _c max	h ₂ max	t/T max
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
M 18F7-D3-P-75	75.00	25.00	11.50	5.72	12.00	30.0	56.6	58.9	20.0	3.0
M 20D1F1.02-P-80	80.00	25.00	16.00	6.00	6.00	25.5	54.7	57.2	18.0	2.5
M 75-D3-P-100	100.00	38.00	18.95	9.53	11.00	38.0	76.2	80.5	26.0	4.0
M 20-D1F2.02-P-80	80.00	25.00	16.00	6.00	6.00	27.8	57.0	59.5	18.0	2.5
M 35F1-P-35	35.00	20.00	16.00	7.00	10.00	30.0	59.0	61.9	18.0	2.5
M 35F7-D1-P-35	35.00	20.00	16.00	8.00	10.00	25.0	56.0	-	18.0	3.0
M 100F11-P-101.6-D3	101.60	47.50	19.00	19.00	15.70	20.0	66.3	71.5	40.0	6.0/5.0
M 100-P-152.4-D3	152.40	47.50	19.00	19.00	18.25	84.8	127.5	132.7	40.0	5.0/4.0
M 100-P-203.2-D3	203.20	47.50	19.00	19.00	18.25	84.8	127.5	132.7	40.0	5.0/4.0
M 160F58-D1.04-P-125	125.00	70.00	34.00	18.00	18.00	71.6	104.0	-	52.0	8.0



HANGZHOU OCEAN INDUSTRY CO., LTD.

Chain No.	抗拉强度 Tensile strength	平均抗拉强度 Average tensile strength	每米长重 Weight per meter
	Q_{min}	Q_{0min}	q
	kN/bf	kN	kg/m
M 18F7-D 3-P-75	18.0/4050	20.00	2.14
M 20D 1F1.02-P-80	20.0/4545	25.00	1.65
M 75-D 3-P-100	75.0/16870	82.50	3.61
M 20-D 1F2.02-P-80	20.0/4545	22.00	1.65
M 35F1-P-35	35.0/7874	39.00	2.47
M 35F7-D 1-P-35	35.0/7874	39.00	2.77
M 100F11-P-101.6-D 3	150.0/33722	165.00	7.60
M 100-P-152.4-D 3	100.0/22496	110.00	6.36
M 100-P-203.2-D 3	100.0/22496	110.00	5.49
M 160F58-D 1.04-P-125	160.0/36364	176.00	17.70