



| CHAIN NO. | PITCH | ROLLER DIA. | WIDTH BETWEEN INNER PLATES | PIN DIA. | PIN LENGTH | | INNER CHAIN PLATE DEPTH | ROW SPACING | ULTIMATE TENSILE STRENGTH | AVERAGE TENSILE STRENGTH | WEIGHT PER METER |
|-----------|-------|-------------|----------------------------|----------|------------|--------|-------------------------|-------------|---------------------------|--------------------------|------------------|
| | P | D1 MAX | B1 MIN | D2 MAX | L MAX | LC MAX | H2 MAX | PT | Q MIN | Q0 | Q |
| | MM | MM | MM | MM | MM | MM | MM | MM | KN | KN | KG/M |
| 08B-2 | 12.7 | 8.51 | 7.75 | 4.45 | 31.2 | 32.2 | 11.8 | 13.92 | 32 | 3.76 | 1.34 |
| 12A-2 | 19.05 | 12.57 | 12.57 | 5.94 | 48.8 | 50.5 | 18 | 22.78 | 63.6 | 83.3 | 2.92 |
| 12AH-2 | 19.05 | 12.57 | 12.57 | 5.94 | 55.3 | 57.1 | 18 | 26.11 | 63.6 | 84.3 | 3.71 |